


TECHNICAL DATA SHEET

ULTRASTRESS PROTECT TRACER

Wastewater pressure pipes with integrated signal wire from PE100-RC/PP

According to PAS 1075 Type 3
Conforms to: EN 12201-2

PRODUCT DESCRIPTION



ULTRASTRESS PROTECT TRACER wastewater pressure pipes made from PE100-RC material with integrated signal wires and added polypropylene (PP) protective layer. PE100-RC/PP material pipes are resistant to long term expansion of cracks, scratching and point type loads which are especially common during assembly of the pipelines using trenchless installation methods (for instance, as a result of friction against the stones that are present in the soil). PE100-RC pipes with PP protective layer provide additional durability against scratching in cases of especially complex installation, e.g. installation in old pipe. Material: High density crack resistant polyethylene PE100-RC with polypropylene (PP) protective layer. Core pipe is black with 4 brown stripes and protective layer is brown with 4 stripes in green colour. Pipes are manufactured according to EN 12201-2, PAS1075.

APPLICATION AREA

ULTRASTRESS PROTECT TRACER pipes are designed for wastewater pressure systems, with recommended installation methods of pulling in the site of the old pipe with or without the destruction of the old pipe according to EN 12889, EN 14457.

PE100-RC / PP

According to PAS 1075:

Type 3

Open product

TECHNICAL DATA SHEET



ULTRASTRESS PROTECT TRACER

Wastewater pressure pipes with integrated signal wire from PE100-RC/PP

According to PAS 1075 Type 3
 Conforms to: EN 12201-2

PRODUCT DIMENSIONS

Pipe dimensions conform to EN 12201-2 specifications. Pipe nominal pressure according to EN12201-2 (with C=1,25 at temperature 20 °C) PN10 bar for SDR 17 pipes and PN16 bar for SDR 11 pipes.



PE100-RC / PP

According to PAS 1075:

Type 3

Open product

Pipe dimensions		PP layer	Main dimensions	Length
dn x en mm		enr mm	Dmr mm	L, m
SDR 17	SDR 11			
32 x 2,0	32 x 3,0	~ 0,9	~ 33,8	6/30/50/60/70/100/150/200/300/400/500/1000/2000
40 x 2,4	40 x 3,7	~ 1,0	~ 42	6/50/100/150/200/300/400/500/1000/2000
50 x 3,0	50 x 4,6	~ 1,0	~ 52	6/50/100/150/200/300/400/500/1000
63 x 3,8	63 x 5,8	~ 1,0	~ 65	6/50/100/150/200/300/400/500
75 x 4,5	75 x 6,8	~ 1,0	~ 77	6/50/100/150/200/300/400/500
90 x 5,4	90 x 8,2	~ 1,5	~ 93	6/12/13,4/50/100/150/200
110 x 6,6	110 x 10,0	~ 1,8	~ 113,6	6/12/13,4/50/100/150/200
125 x 7,4	125 x 11,4	~ 2,0	~ 129	6/12/13,4/50/100
160 x 9,5	160 x 14,6	~ 2,0	~ 164	6/12/13,4/18/20/50/100
180 x 10,7	180 x 16,4	~ 2,0	~ 184	6/12/13,4/18/20/50
200 x 11,9	200 x 18,2	~ 2,0	~ 204	6/12/13,4/18/20/50
225 x 13,4	225 x 20,5	~ 3,0	~ 231	6/12/13,4/18/20
250 x 14,8	250 x 22,7	~ 3,0	~ 256	6/12/13,4/18/20
280 x 16,6	280 x 25,4	~ 3,0	~ 286	6/12/13,4/18/20
315 x 18,7	315 x 28,6	~ 3,0	~ 321	6/12/13,4/18/20
355 x 21,1	355 x 32,2	~ 3,0	~ 363	6/12/13,4/18/20
400 x 23,7	400 x 36,3	~ 3,0	~ 406	6/12/13,4/18/20
450 x 26,7	450 x 40,9	~ 3,5	~ 457	6/12/13,4/18/20
500 x 29,7	500 x 45,4	~ 3,5	~ 507	6/12/13,4/18/20
560 x 33,2	560 x 50,8	~ 3,7	~ 567,4	6/12/13,4/18/20
630 x 37,4	630 x 57,2	~ 4,0	~ 638	6/12/13,4/18/20
710 x 42,1	710 x 64,5	~ 5,0	~ 720	6/12/13,4/18/20
800 x 47,2	800 x 72,6	~ 5,0	~ 810	6/12/13,4/18/20
900 x 53,3	900 x 81,7	~ 5,5	~ 911	6/12/13,4/18/20
1000 x 59,3	1000 x 90,8	~ 6,0	~ 1012	6/12/13,4/18/20
1200 x 71,1	-	~ 6,5	~ 1213	6/12/13,4/18/20

TECHNICAL DATA SHEET

ULTRASTRESS PROTECT TRACER

Wastewater pressure pipes with integrated signal wire from PE100-RC/PP

According to PAS 1075 Type 3
 Conforms to: EN 12201-2

PRODUCT PARAMETERS

Parameter	Value	Test method
Material	Core pipe: PE100-RC Outer layer: PP	PAS 1075
Hydrostatic pressure resistance (80 °C, 5,4 MPa)	>165 h	EN ISO 1167-1 EN ISO 1167-2
Tensile elongation	≥350%	EN ISO 6259-1 EN ISO 6259-3
Resistance to crack growth (80 °C, 4 MPa, 2% Arkopal N-100)	>8760 h	ISO 16770
Resistance to slow crack growth (80 °C, 9,2 bar)	>8760 h	EN ISO 13479
Mass flow rate (MFR) (5 kg, 190 °C, 10 min)	0.2-0,4g	EN ISO 1133
Oxidation induction time (200 °C)	≥20 min	EN ISO 11357-6
Longitudinal reversion (e _r ≤16 mm, 110 °C)	≤3%	EN ISO 2505
Chemical resistance	pH 2 ≥ pH ≥ pH 12	ISO/TR 10358

PRODUCT MARKING

PE100-RC / PP

According to PAS 1075:

Type 3

Open product

Protective layer marking

Aspect	Marking
Standard number	EN 12201
Material requirements and type	PAS 1075 Type 3
Manufacturers information	EVOPIPES
Product identification	ULTRASTRESS PROTECT TRACER
Signal wire resistance	3.6 Ω x m
Core pipe dimension (diameter x wall thickness)	e.g. 110 x 6,6
SDR series	e.g. SDR 17
Extrusion type	PEELABLE PP LAYER
Material	PE100-RC/PP
Core pipe pressure rating (bar)	e.g. PN10
Intended application (P-wastewater)	P
Date of production	date
QA organization signature	Nordic Poly Mark

Core pipe marking

Standard number	EN 12201
Material requirements and type	PAS 1075 Type 1
Manufacturers information	EVOPIPES
Dimensions (diameter x wall thickness)	e.g. 110 x 6,6
SDR series	e.g. SDR 17
Material	PE100-RC
Pressure rating (bar)	e.g. PN10
Intended application (P-wastewater)	P
Date of production (dd/mm/yy)	date
QA organization signature	Nordic Poly Mark